

PRO 9020IP-4MPX 4MPX Xtreme Professional IP66 IP Dome Camera



- H.264/H.265
- 4 Megapixel 2688x1520
- Vandalproof
- Wide Dynamic Range
- Bidirectional Audio
- BNC Output
- Alarm in/out
- 3 a 12 mm Motorized Varifocal Lens
- Day/Night - 15 mts IR Range
- IP 66 - Outdoor
- ROI
- FREE Siera DDNS
- FREE CMS for 64 Cameras
- FREE App for iOS and Android
- PoE
- SD Card Max 32GB
- ONVIF

Designed for outdoor professional applications where the high resolution, varifocal lens, night vision, wide dynamic range and bandwidth control are needed.

| | |
|-------------------------|---|
| Sensor: | 4 Megapixel 2688x1520 |
| Lens: | 3 to 12 mm Motorized |
| Electronic Iris: | 1/25s – 1/30,000s |
| Electronic Shutter: | Auto / 1/5 – 1/50, 0000 |
| Illumination Min.: | 0.1Lux (F1.2) |
| Resolution: | 2688x1520 |
| FPS: | 1–30fps (NTSC) / 1–25fps (PAL) |
| Video Compression: | H.264 / H.265 |
| Day/Night Function: | ICR Filter |
| Simultaneous Recording: | SD, FTP Server, CMS, RTSP |
| Audio Compression: | G.711 |
| Audio In: | 1 RCA |
| Audio Out: | 1 RCA |
| Ethernet: | 1 ch 10/100M, RJ45 |
| TCP/IP: | IPv4 / IPv6 |
| Network Protocols: | HTTP, TCP/IP, UDP/IP, RTSP, FTP, DHCP, NTP, PPPoE, NTP, Unicast and Multicast RFC2326, Quicktime, VLC Safari, Chrome, IE, Firefox |
| RTSP Video: | |
| Supported Browser: | |
| Privacy Zones: | 5 zonas |
| OS: | Linux |
| Alarm In: | 1 Channel |
| Alarm Out: | 1 Channel |
| Video Output: | Service BNC Output |
| Vandalproof Approval: | IK10 |
| Power: | DC12V – 520mA / PoE |
| Working Temperature: | –20° C / 60° C |
| Operating Humidity: | 10% / 85% |
| Dimensions: | 130 x 112 mm |
| Weight: | 0,85 Kg |



H.265

4MPX



WDR



Onvif

DDNS



DATA SUBJECT TO CHANGE WITHOUT PRIOR NOTICE / PRO9020IP-2MPX-0017